

# DIMENSIONS AND WEIGHTS

STABIFLEX Type	A	B	C	D	p	KR <sup>+20°</sup> **)	RA (Incl. pre-load)	H	L <sub>fmax</sub>	L <sub>s</sub> Without support	L <sub>s</sub> With support	Weight Hose kg/m	Weight Flanges kg/Pair
0.0	30	20	26	16	25	55	120	144	1000	2000	4000	~ 0.6	~ 0.1
1.0	50	30	43	23	30	72 110 165	160 235 345	194 269 379	1500	3000	6000	~1.25	~ 0.2
1.1	50	50	45	45	50	110	240	294	2000	4000	8000	~ 1.7	~ 0.3
2.0	80	45	73	38	45	110 220 275	240 460 570	290 510 620	2000	4000	8000	~ 2.25	~ 0.5
2.1	85	60	80	55	65	165	350	415	2500	5000	10.000	~ 2.4	~ 0.6
2.2	95	50	90	45	60	130	280	335	2000	4000	8000	~ 2.9	~ 0.6
3.0	110	60	102	52	60	155 250 330	335 525 685	400 590 750	2500	5000	10.000	~ 3.6	~ 1.0
3.1	115	80	109	74	80	220	465	550	2500	5000	10.000	~ 3.8	~ 1.2
4.0	170	80	162	72	80	205	435	520	2500	5000	10.000	~ 5.6	~1.7
4.1	175	110	167	102	80	285	600	717	2500	5000	10.000	~ 5.8	~ 3.9